






Visible Surfaces
in this direction





SCALE 1:2



SCALE 1:2



- (60) ∇Critical Characteristic dimension no.2,50
(61) General inner bending radius : 0.5 mm
(62) Tolerances for not specified dimensions: ± 0.25
(63) Corner rounds not specified: $R1 \pm 0.2$
(64) Burrs must be removed and sharp edges must be polish
(65) Part must be washed and degreased
(66) No impact marks acceptable
(67) Scratches to be avoided on visible surfaces
(68) Material specification:
1.5 mm Sheet acc. to EN 10346 DX51D AZ150-N-A-C
(69) Not specified dimensions according to unfolded part
(70) Part Weight : 0.09 Kg
(71) Has to comply with RoHS directive

PDM controlled drawing. Hard copy not valid without frozen date in ID Stamp		Projection 	Scale 1:1	Size A2	Material _____ See Note _____	
						
					Designation \ Name	
					Power decoupling plate J1	
Replace						
Designer	Zhao Bo 2012-07-18					
Confidential: Property of Danfoss Power Electronics A/S, Grasten, Denmark. Not to be handed over to, copied or used by third party. Two- or three dimensional reproduction of contents to be authorized by Danfoss Power Electronics A/S.					No.	132B3594
						Rev. 002
					Sheet 1 of 1	

Model: 132B3594 PART